

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method of updating a routing table, the method comprising the computer-implemented steps of:
selecting, from a set of routers, a particular router that is associated with a first actual time that is a shortest time among all times associated with routers in the set of routers;
wherein the first actual time has been updated with a previous actual time taken for a previous data packet to travel to a previous destination indicated by the previous data packet;
sending a first data packet to the particular router;
receiving a second data packet that indicates a second actual time taken for the first data packet to travel to a destination indicated by the first data packet;
wherein the destination indicated by the first data packet is the same as the previous destination indicated by the previous data packet;
wherein the second data packet is sent from the destination indicated by the first data packet;
updating the first actual time based on the second actual time; and
updating the routing table based on information contained in the second data packet;
wherein the method is performed by one or more computing devices.
2. (Original) The method of Claim 1, further comprising:
updating, based on information contained in the second data packet, a path associated with both the destination and the particular router.
3. (Original) The method of Claim 1, further comprising:
updating, based on information contained in the second data packet, an indication of an amount of bandwidth available on a path taken by the second data packet.
4. (Original) The method of Claim 1, further comprising:

updating, based on information contained in the second data packet, an indication of whether a path taken by the first data packet is feasible.

5. (Previously Presented) The method of Claim 1, further comprising:
updating, based on information contained in the second data packet, a list of
routers that indicates all routers in a path taken by the first data packet
from a router that sent the first data packet to a present router.
6. (Original) The method of Claim 1, further comprising:
updating the second data packet to indicate an amount of bandwidth available on
a path taken by the second data packet.
7. (Original) The method of Claim 1, further comprising:
updating the second data packet to indicate whether a path taken by the first data
packet is feasible.
8. (Currently Amended) A method of updating a routing table, the method
comprising the computer-implemented steps of:
for each neighbor router in a set of neighbor routers, associating the neighbor
router with an amount of time predicted to be required for a data packet to
travel to a specified destination if the data packet is transmitted through
the neighbor router;
receiving a first data packet that indicates the specified destination;
in response to receiving the first data packet, selecting, from the set of neighbor
routers, a particular neighbor router that is associated with a first amount
of actual time that is a lowest amount of time, relative to the specified
destination, among amounts of time associated with neighbor routers in
the set of neighbor routers;
wherein the lowest amount of time has been updated with a previous amount of
actual time taken for a previous data packet to travel to the specified
destination;
sending the first data packet to the particular neighbor router;

receiving a second data packet that indicates a second amount of actual time taken for the first data packet to travel to the specified destination;
wherein the second data packet is sent from the specified destination;
updating, based on the second amount of actual time, the first amount of actual time; and
updating, based on information contained in the second data packet, the routing table;

wherein the method is performed by one or more computing devices.

9. (Currently Amended) A method of updating a routing table, the method comprising the computer-implemented steps of:
for each neighbor router in a set of neighbor routers, associating the neighbor router with an amount of time predicted to be required for a data packet to travel to a specified destination if the data packet is transmitted through the neighbor router;
receiving a forward ant data packet that indicates the specified destination;
selecting, based on one or more first specified criteria, a subset of the set of neighbor routers;
in response to receiving the forward ant data packet, selecting, from the subset of neighbor routers, a particular neighbor router that is associated with a first amount of actual time that is a lowest amount of time, relative to the specified destination, among amounts of time associated with neighbor routers in the subset of neighbor routers;
wherein the lowest amount of time has been updated with a previous amount of actual time taken for a previous data packet to travel to the specified destination;
sending the forward ant data packet to the particular neighbor router;
receiving a backward ant data packet that indicates a second amount of actual time taken for the forward ant data packet to travel to the specified destination;
wherein the backward ant data packet is sent from the specified destination;

determining, based on information indicated in the backward ant data packet,
whether one or more second specified criteria are satisfied; and
if the one or more second specified criteria are satisfied, then performing steps
comprising:
updating, based on the second amount of actual time, the first amount of
actual time; and
if one or more third specified criteria are satisfied, then updating, based on
information indicated in the backward ant data packet, the routing
table;
wherein the method is performed by one or more computing devices.

10. (Original) The method of Claim 9, wherein the one or more first specified criteria comprise a criterion that no neighbor router in the subset of neighbor routers is contained in a list of routers that have already been visited by the forward ant data packet.
11. (Previously Presented) The method of Claim 9, further comprising:
determining whether any neighbor router in the set of neighbor routers is
associated with an amount of time that is lower than the first amount of
actual time; and
if any neighbor router in the set of neighbor routers is associated with an amount
of time that is lower than the first amount of actual time, then updating the
forward ant data packet to indicate a present router in a loop-avoidance
router field of the forward ant data packet.
12. (Original) The method of Claim 11, wherein a loop-avoidance router field of the
backward ant data packet indicates a router indicated by the loop-avoidance router
field of the forward ant data packet.
13. (Original) The method of Claim 12, wherein the one or more second specified
criteria comprise a criterion that the router indicated by the loop-avoidance router

field of the backward ant data packet is not contained in a list of routers that the forward ant visited after visiting a present router.

14. (Previously Presented) The method of Claim 9, wherein the one or more third specified criteria comprise a criterion that the second amount of actual time is lower than any other amount of time, relative to the specified destination, among amounts of time associated with neighbor routers in the set of neighbor routers.
15. (Original) The method of Claim 9, further comprising:
determining whether a router from which the backward ant data packet was received matches a router associated with the destination in the routing table; and
if the router from which the backward ant data packet was received does not match the router associated with the destination in the routing table, then updating a path feasibility flag of the backward ant to indicate that a path taken by the forward ant is not feasible.
16. (Original) The method of Claim 15, wherein the one or more third specified criteria comprise a criterion that the path feasibility flag of the backward ant indicates that the path taken by the forward ant is feasible.
17. (Original) The method of Claim 9, wherein the one or more third specified criteria comprise a criterion that a path taken by the forward ant data packet from a present router to the specified destination does not include any routers that are identified in a potential upstream node list.
18. (Currently Amended) A volatile or non-volatile computer-readable medium ~~carrying~~ storing one or more sequences of instructions for updating a routing table, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:
selecting, from a set of routers, a particular router that is associated with a first actual time that is a shortest time among all times associated with routers in the set of routers;

wherein the first actual time has been updated with a previous actual time taken for a previous data packet to travel to a previous destination indicated by the previous data packet;
sending a first data packet to the particular router;
receiving a second data packet that indicates a second actual time taken for the first data packet to travel to a destination indicated by the first data packet;
wherein the destination indicated by the first data packet is the same as the previous destination indicated by the previous data packet;
wherein the second data packet is sent from the destination indicated by the first data packet;
updating, based on the second actual time, the first actual time; and
updating, based on information contained in the second data packet, the routing table.

19. (Previously Presented) An apparatus for updating a routing table, comprising:
means for selecting, from a set of routers, a particular router that is associated with a first actual time that is a shortest time among all times associated with routers in the set of routers;
wherein the first actual time has been updated with a previous actual time taken for a previous data packet to travel to a previous destination indicated by the previous data packet;
means for sending a first data packet to the particular router;
means for receiving a second data packet that indicates a second actual time taken for the first data packet to travel to a destination indicated by the first data packet;
wherein the destination indicated by the first data packet is the same as the previous destination indicated by the previous data packet;
wherein the second data packet is sent from the destination indicated by the first data packet;
means for updating, based on the second actual time, the first actual time; and
means for updating, based on information contained in the second data packet, the routing table.

20. (Previously Presented) An apparatus for updating a routing table, comprising:
a network interface that is coupled to a data network for receiving one or more
packet flows therefrom;
a processor;
one or more stored sequences of instructions which, when executed by the
processor, cause the processor to carry out the steps of:
selecting, from a set of routers, a particular router that is associated with a
first actual time that is a shortest time among all times associated
with routers in the set of routers;
wherein the first actual time has been updated with a previous actual time
taken for a previous data packet to travel to a previous destination
indicated by the previous data packet;
sending a first data packet to the particular router;
receiving a second data packet that indicates a second actual time taken for
the first data packet to travel to a destination indicated by the first
data packet;
wherein the destination indicated by the first data packet is the same as the
previous destination indicated by the previous data packet;
wherein the second data packet is sent from the destination indicated by
the first data packet;
updating, based on the second actual time, the first actual time; and
updating, based on information contained in the second data packet, the
routing table.
21. (Previously Presented) The apparatus of Claim 20, wherein the stored sequences
of instructions include instructions which, when executed by the processor, cause
the processor to further carry out:
updating, based on information contained in the second data packet, a path
associated with both the destination and the particular router.
22. (Previously Presented) The apparatus of Claim 20, wherein the stored sequences
of instructions include instructions which, when executed by the processor, cause

the processor to further carry out:

updating, based on information contained in the second data packet, an indication of an amount of bandwidth available on a path taken by the second data packet.

23. (Previously Presented) The apparatus of Claim 20, wherein the stored sequences of instructions include instructions which, when executed by the processor, cause the processor to further carry out:
updating, based on information contained in the second data packet, an indication of whether a path taken by the first data packet is feasible.
24. (Previously Presented) The apparatus of Claim 20, wherein the stored sequences of instructions include instructions which, when executed by the processor, cause the processor to further carry out:
updating, based on information contained in the second data packet, a list of routers that indicates every router in a path taken by the first data packet from a router that sent the first data packet to a present router.
25. (Previously Presented) The apparatus of Claim 20, wherein the stored sequences of instructions include instructions which, when executed by the processor, cause the processor to further carry out:
updating the second data packet to indicate an amount of bandwidth available on a path taken by the second data packet.